

**TREMCO ROOF SYSTEMS SUITABLE FOR USE
OVER ELASTIZELL LIGHT WEIGHT CONCRETE**



(NB: A mechanically fastened Composite Ply base sheet is required prior to installing one of the following Tremco Roof Systems)

<u>SYSTEM NAME</u>	<u>MEMBRANE TYPE</u>	<u>FLASHING TYPE</u>	<u>WARRANTY</u>
HOT-APPLIED			
BUR	4 PLY #15 OR TYPE IV FELT PREMIUM III OR TYPE III ASPHALT INTERPLY AND FLOOD/GRAVEL	TRA/ASPHALT	5 YEAR
	4 PLY #15 OR TYPE IV FELT PREMIUM III OR TYPE III ASPHALT INTERPLY AND GLAZE COAT (20#) THERMASTIC 50, 100 OR POWERPLY HOT MELT FLOOD/GRAVEL	TRA/THERMASTIC 50, 100 OR POWERPLY HOT MELT	10 YEAR
	COMPOSITE PLY BASE, 2 PLY TYPE IV PREMIUM III OR TYPE III ASPHALT INTERPLY AND GLAZE COAT (20#) THERMASTIC 50, 100 OR POWERPLY HOT MELT FLOOD/GRAVEL	TRA/THERMASTIC 50, 100 OR POWERPLY HOT MELT	10 YEAR
	COMPOSITE PLY BASE, 2 PLY TYPE IV POWERPLY OR THERMASTIC 100 INTERPLY AND FLOOD/GRAVEL	TRA/POWERPLY HOT MELT OR THERMASTIC 100	15-20 YEAR
MB	2 PLY 180 GM SMOOTH BASE, THERMASTIC 50, 100 OR POWERPLY HOT MELT INTERPLY/FLOOD/GRAVEL	TRA/THERMASTIC 50, 100 OR POWERPLY HOT MELT	10 YEAR
	GRANULATED MB CAP PLY, SMOOTH BASE PLY, THERMASTIC 50, 100 OR POWERPLY HOT MELT INTERPLY.	TRA OR 2 PLY MB/THERMASTIC 50, 100 OR POWERPLY HOT MELT	10-15 YEAR
COLD-APPLIED			
BUR	3 PLY COMPOSITE PLY, BURMASTIC ADHESIVE (REG OR SF) INTERPLY, FLOOD COAT (REG ONLY), GRAVEL	TRA/TREMLAR V	15-20 YEAR
MB	2 PLY 180 GM SMOOTH BASE, BURMASTIC ADH (REG OR SF) INTERPLY, FLOOD COAT (REG ONLY), GRAVEL	TRA/TREMLAR V	10 YEAR
	GRANULATED MB CAP PLY, SMOOTH BASE PLY, BURMASTIC ADHESIVE INTERPLY	TRA OR 2 PLY MB/ TREMLAR V	10-15 YEAR

(Check with Tremco regarding other options for membrane surfacing such as smooth reflective or gravelled reflective finishes)